



P.C.B LAYOUT REF

Specifications:
 Housing: LCP UL94-V0 Color: Nature
 Contact: Phosphor Bronze
 Operating Voltage: 50V AC/DC
 Current Rating: 1A AC/DC
 Withstand Voltage: 250V AC/Minute
 Contact Resistance: $\leq 20\text{m}\Omega$
 Insulation resistance: $\geq 100\text{m}\Omega$
 Operating Temperature: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$

NO. of Contacts (n)	Dimensions		
	A	B	C
002	1.0	4.0	3.3
003	2.0	5.0	4.3
004	3.0	6.0	5.3
005	4.0	7.0	6.3
006	5.0	8.0	7.3
007	6.0	9.0	8.3
008	7.0	10.0	9.3
009	8.0	11.0	10.3
010	9.0	12.0	11.3
011	10.0	13.0	12.3
012	11.0	14.0	13.2
013	12.0	15.0	14.2
014	13.0	16.0	15.2
015	14.0	17.0	16.2
016	15.0	18.0	17.2
017	16.0	19.0	18.2
018	17.0	20.0	19.2
019	18.0	21.0	20.2
020	19.0	22.0	21.2

一般公差
 TOLERANCES
 X. ± 0.40 .XX ± 0.20
 .X ± 0.30 .XXX ± 0.10
 ANGLES $\pm 2^{\circ}$

检验尺寸标示
 SYMBOLS \odot \ominus INDICATE
 CLASSIFICATION DIMENSION

\odot MARK IS CRITICAL DIM.
 \ominus MARK IS MAJOR DIM.

表面处理 (FINISH)

深圳市宏利电子有限公司
 Shenzhen Holy Electronic Co.,Ltd

工程图号 SH10ALB-nP 制图 (DR) '08/5/16
 品名 SH1.0A-nP 立贴 审核 (CHKD)

TITLE SH1.0mm Pitch LB A TYPE FOR SMT CONN 核准 (APPD) Rigo Lu

比例 (SCALE) 1:1 单位 (UNITS) mm 张数 (SHEET) 1 OF 1 尺寸 (SIZE) A4 版数 (REV) 0

修订 REV	修改摘要 REVISION DESCRIPTION	日期 DATE	签名 SIGNATURE
△	-	-	-