



PCB LAYOUT

SPECIFICATIONS

- 1、Current Rating: 7A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- 4、Contact Resistance: $20\text{m}\Omega$ Max
- 5、Insulation Resistance: $1000\text{M}\Omega$ Min
- 6、Withstanding Voltang: 1500V AC/minute
- 7、Material: Wafer Nylon66, UL94V-0
PIN Brass Tin-plated

编号	尺寸 (mm)	
	A	B
A3961-02A	3.96	7.92
A3961-03A	7.92	11.88
A3961-04A	11.88	15.84
A3961-05A	15.84	19.80
A3961-06A	19.80	23.76
A3961-07A	23.76	27.72
A3961-08A	27.72	31.68
A3961-09A	31.68	35.64
A3961-10A	35.64	39.60
A3961-11A	39.60	43.56
A3961-12A	43.56	47.52

制图 DRAWN	变更内容 DESCRIPTION	日期 DATE	GENERAL TOLERANCE		制图 DRAWING	钱岳生			料号 PART NO.	A3961-NA		版本 REV.	A
			X \pm 0.25	X \pm 2'		2013. 07. 01	张名	品名 TITLE	VH直针 WAFER DIP TYPE		页次 SHEET	1/1	
			.X \pm 0.20	.X \pm 1'	审核 CHECK	2013. 07. 03	张名	客户料号 CUTL. NO.					
			.XX \pm 0.15	.XX \pm 0.5'	核准 APPROVAL	2013. 07. 05	张名	深圳市宏利电子有限公司 MM 比例 SCALE 1:1					
			.XXX \pm 0.10	.XXX \pm 0.5'	单位 UNITS								