



RECOMMENDED PC BOARD

Specifications:

Housing: LCP UL94-V0 Color: Black
 Contact: Phosphor Bronze Gold Plated
 Operating Voltage: 500V AC/DC
 Current Rating: 1A AC/DC
 Withstand Voltage: 500V AC/Minute
 Contact Resistance: $\leq 20\text{m}\Omega$
 Insulation resistance: $\geq 500\text{m}\Omega$
 Operating Temperature: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$

P数	尺寸			
	A	B	C	D
004	7.5	10.5	11.5	14.5
005	10.0	13.0	14.0	17.0
006	12.5	15.5	16.5	19.5
007	15.0	18.0	19.0	22.0
008	17.5	20.5	21.5	24.5
009	20.0	23.0	24.0	27.0
010	22.5	25.5	26.5	29.5
011	25.0	28.0	29.0	32.0
012	27.5	30.5	31.5	34.5
013	30.0	33.0	34.0	37.0
014	32.5	35.5	36.5	39.5
015	35.0	38.0	39.0	42.0
016	37.5	40.5	41.5	44.5

一般公差
TOLERANCES
X .±0.40 .XX ±0.20
.X ±0.30 .XXX ±0.10
ANGLES ±2°

深圳市宏利电子有限公司
Shenzhen Holy Electronic Co.,Ltd

检验尺寸标示
SYMBOLS \odot \ominus INDICATE
CLASSIFICATION DIMENSION

工程图号 HL25M-nP

制图 (DR) *10/03/22
审核 (CHKD)

\odot MARK IS CRITICAL DIM.
 \ominus MARK IS MAJOR DIM.

品名 2.5mm - nP 镀金母座

核准 (APPD) Rigo Lu

表面处理 (FINISH)

比例 (SCALE) 1:1
单位 (UNITS) mm

张数 (SHEET) 1 OF 1
SIZE A4
REV 0

修订 REV	修改摘要 REVISION DESCRIPTION	日期 DATE	签名 SIGNATURE
-	-	-	-