



PCB LAYOUT

Specifications:
 Operating Voltage:250V AC/DC
 Current Rating:2A AC/DC
 Withstand Voltage:800V AC/Minute
 Contact Resistance:≤20mΩ
 Insulation resistance:≥500mΩ
 Operating Temperature:-25℃~+85℃
 Material:PA66 UL94V-0
 PIN Brass Tin-plated

P数	尺寸 (mm)	
	A	B
2	2.0	6.0
3	4.0	8.0
4	6.0	10.0
5	8.0	12.0
6	10.0	14.0
7	12.0	16.0
8	14.0	18.0
9	16.0	20.0
10	18.0	22.0
11	20.0	24.0
12	22.0	26.0
13	24.0	28.0
14	26.0	30.0
15	28.0	32.0
16	30.0	34.0

一般公差
 TOLERANCES
 X. ±0.40 .XX ±0.20
 .X ±0.30 .XXX ±0.10
 ANGLES ±2°

深圳市宏利电子有限公司
 Shenzhen Holy Electronic Co.,Ltd

检验尺寸标示
 SYMBOLS INDICATE
 CLASSIFICATION DIMENSION

工程图号 PH20-nA

制图 (DR) *10/03/22

MARK IS CRITICAL DIM.
 MARK IS MAJOR DIM.

品名 PH2.0-nA 直针

审核 (CHKD)

TITLE PH2.0mm Pitch A DIP CONN

核准 (APPD)

Rigo Lu

表面处理 (FINISH)

比例 (SCALE) 1:1

张数 (SHEET) 1 OF 1

单位 (UNITS) mm

尺寸 (SIZE) A4

修订 (REV)

修改摘要 (REVISION DESCRIPTION)

日期 (DATE)

签名 (SIGNATURE)

修订 (REV)	修改摘要 (REVISION DESCRIPTION)	日期 (DATE)	签名 (SIGNATURE)
-	-	-	-